

DNES3-S8□


Fuse for battery and battery system protection



Product Profile

DNES3-S8□ Fuse for battery and battery system protection, suitable for battery system, with rated voltage of DC1500V and rated current of 100A~1000A, used for short circuit protection of battery and battery system.

Model and meaning



Operational condition

1. Working humidity range: At a maximum temperature of 40°C, the relative humidity does not exceed 50%. At a maximum temperature of 20°C, the relative humidity should not exceed 90%.
2. Normal operating temperature range: -5°C to 40°C. Permissible temperature range: -40°C to 80°C.
3. Altitude: no more than 2000m. When the altitude exceeds this value:
 - 1) The temperature rise of the fuse increases by about 0.5k for every 100 meters above sea level.
 - 2) For every 100 meters of elevation increase, the ambient temperature decreases by about 0.5 °C on average.
 - 3) Under normal circumstances, fuses used in open environments can ignore the effect of altitude on rated current and still be selected in accordance with standard conditions.
 - 4) For fuses used in closed environments, if the ambient air temperature of the box or the temperature inside the box does not decrease significantly with the elevation, it can still reach more than 40°C, it is necessary to reduce the rated current capacity. Fuse rated current selection formula:

$$I = I_n \times \left(1 - \frac{h-2000}{100} \times \frac{0.5}{100}\right)$$

DNESS3-S8J

Fuse for battery and battery system protection



Rated Voltage	DC 1500V
Rated Current	100A, 125A, 160A, 200A, 250A, 315A, 350A, 400A, 450A, 500A, 550A, 630A, 700A, 800A, 900A, 1000A
Protection Category	aBat
Breaking Capacity	250kA
Reference Standard	IEC 60269-7

Product parameter


Specification and model	size	Rated voltage V	Rated current A	Rated breaking capacity kA	forearc I ² t kA ² s	fusing I ² t kA ² s	In Dissipated power W
DNESS3-S8J-100	3	DC 1500V	100	250kA	2	9	55
DNESS3-S8J-125			125		3.6	16	68
DNESS3-S8J-160			160		6	26	85
DNESS3-S8J-200			200		10	43	102
DNESS3-S8J-250			250		17	64	113
DNESS3-S8J-315			315		28	107	132
DNESS3-S8J-350			350		37.2	177	146
DNESS3-S8J-400			400		62	253	153
DNESS3-S8J-450			450		77.5	291	164
DNESS3-S8J-500			500		129	485	188
DNESS3-S8J-550			550		184	693	200
DNESS3-S8J-630			630		230	990	215
DNESS3-S8J-700			700		328	1238	267
DNESS3-S8J-800			800		468	1768	298
DNESS3-S8J-900			900		667	2072	319
DNESS3-S8J-1000			1000		846	2590	340

Overall dimensions (mm)


Installation method

Bolted connection type


Time-current characteristic curve



Note: The deviation range of the time current curve is $\pm 10\%$ of the current



Cut-off current characteristic curve



Note: The deviation range of the truncated current curve is $\pm 10\%$ of the peak current

DNESS3-S8L

Fuse for battery and battery system protection



Rated Voltage	DC 1500V
Rated Current	100A, 125A, 160A, 200A, 250A, 315A, 350A, 400A, 450A, 500, 550, 630A, 700A, 800A, 900A, 1000A
Protection Category	aBat
Breaking Capacity	250kA
Reference Standard	IEC 60269-7

Product parameter


Specification and model	size	Rated voltage V	Rated current A	Rated breaking capacity kA	forearc I ² t kA ² s	fusing I ² t kA ² s	In Dissipated power W
DNESS3-S8L-100	3	DC 1500V	100	250kA	2	9	55
DNESS3-S8L-125			125		3.6	16	68
DNESS3-S8L-160			160		6	26	85
DNESS3-S8L-200			200		10	43	102
DNESS3-S8L-250			250		17	64	113
DNESS3-S8L-315			315		28	107	132
DNESS3-S8L-350			350		37.2	177	146
DNESS3-S8L-400			400		62	253	153
DNESS3-S8L-450			450		77.5	291	164
DNESS3-S8L-500			500		129	485	188
DNESS3-S8L-550			550		184	693	200
DNESS3-S8L-630			630		230	990	215
DNESS3-S8L-700			700		328	1238	267
DNESS3-S8L-800			800		468	1768	298
DNESS3-S8L-900			900		667	2072	319
DNESS3-S8L-1000			1000		846	2590	340

Overall dimensions (mm)


Installation method

Bolted connection type


Time-current characteristic curve



Note: The deviation range of the time current curve is $\pm 10\%$ of the current



Cut-off current characteristic curve



Note: The deviation range of the truncated current curve is $\pm 10\%$ of the peak current

DNESS3-S8N

Fuse for battery and battery system protection



Rated Voltage	DC 1500V
Rated Current	100A, 125A, 160A, 200A, 250A, 315A, 350A, 400A, 450A, 500, 550, 630A, 700A, 800A, 900A, 1000A
Protection Category	aBat
Breaking Capacity	250kA
Reference Standard	IEC 60269-7

Product parameter


Specification and model	size	Rated voltage V	Rated current A	Rated breaking capacity kA	forearc I ² t kA ² s	fusing I ² t kA ² s	In Dissipated power W
DNESS3-S8N-100	3	DC 1500V	100	250kA	2	9	55
DNESS3-S8N-125			125		3.6	16	68
DNESS3-S8N-160			160		6	26	85
DNESS3-S8N-200			200		10	43	102
DNESS3-S8N-250			250		17	64	113
DNESS3-S8N-315			315		28	107	132
DNESS3-S8N-350			350		37.2	177	146
DNESS3-S8N-400			400		62	253	153
DNESS3-S8N-450			450		77.5	291	164
DNESS3-S8N-500			500		129	485	188
DNESS3-S8N-550			550		184	693	200
DNESS3-S8N-630			630		230	990	215
DNESS3-S8N-700			700		328	1238	267
DNESS3-S8N-800			800		468	1768	298
DNESS3-S8N-900			900		667	2072	319
DNESS3-S8N-1000			1000		846	2590	340

Overall dimensions (mm)


Installation method

螺栓连接挂钩型


Time-current characteristic curve



Note: The deviation range of the time current curve is $\pm 10\%$ of the current



Cut-off current characteristic curve



Note: The deviation range of the truncated current curve is $\pm 10\%$ of the peak current

DNESS3-S8Q

Fuse for battery and battery system protection



Rated Voltage	DC 1500V
Rated Current	100A, 125A, 160A, 200A, 250A, 315A, 350A, 400A, 450A, 500, 550, 630A, 700A, 800A, 900A, 1000A
Protection Category	aBat
Breaking Capacity	250kA
Reference Standard	IEC 60269-7

Product parameter


Specification and model	size	Rated voltage V	Rated current A	Rated breaking capacity kA	forearc I ² t kA ² s	fusing I ² t kA ² s	In Dissipated power W
DNESS3-S8Q-100	3	DC 1500V	100	250kA	2	9	55
DNESS3-S8Q-125			125		3.6	16	68
DNESS3-S8Q-160			160		6	26	85
DNESS3-S8Q-200			200		10	43	102
DNESS3-S8Q-250			250		17	64	113
DNESS3-S8Q-315			315		28	107	132
DNESS3-S8Q-350			350		37.2	177	146
DNESS3-S8Q-400			400		62	253	153
DNESS3-S8Q-450			450		77.5	291	164
DNESS3-S8Q-500			500		129	485	188
DNESS3-S8Q-550			550		184	693	200
DNESS3-S8Q-630			630		230	990	215
DNESS3-S8Q-700			700		328	1238	267
DNESS3-S8Q-800			800		468	1768	298
DNESS3-S8Q-900			900		667	2072	319
DNESS3-S8Q-1000			1000		846	2590	340

Overall dimensions (mm)


Installation method

螺栓连接挂钩型


Time-current characteristic curve



Note: The deviation range of the time current curve is $\pm 10\%$ of the current



Cut-off current characteristic curve



Note: The deviation range of the truncated current curve is $\pm 10\%$ of the peak current

DNESS3-S8R

Fuse for battery and battery system protection



Rated Voltage	DC 1500V
Rated Current	100A, 125A, 160A, 200A, 250A, 315A, 350A, 400A, 450A, 500, 550, 630A, 700A, 800A, 900A, 1000A
Protection Category	aBat
Breaking Capacity	DC 250kA
Reference Standard	IEC 60269-7

Product parameter


Specification and model	size	Rated voltage V	Rated current A	Rated breaking capacity kA	forearc I^2t kA ² s	fusing I^2t kA ² s	In Dissipated power W
DNESS3-S8R-100	3	DC 1500V	100	250kA	2	9	55
DNESS3-S8R-125			125		3.6	16	68
DNESS3-S8R-160			160		6	26	85
DNESS3-S8R-200			200		10	43	102
DNESS3-S8R-250			250		17	64	113
DNESS3-S8R-315			315		28	107	132
DNESS3-S8R-350			350		37.2	177	146
DNESS3-S8R-400			400		62	253	153
DNESS3-S8R-450			450		77.5	291	164
DNESS3-S8R-500			500		129	485	188
DNESS3-S8R-550			550		184	693	200
DNESS3-S8R-630			630		230	990	215
DNESS3-S8R-700			700		328	1238	267
DNESS3-S8R-800			800		468	1768	298
DNESS3-S8R-900			900		667	2072	319
DNESS3-S8R-1000			1000		846	2590	340

Overall dimensions (mm)


Installation method

Bolted connection type


Time-current characteristic curve



Note: The deviation range of the time current curve is $\pm 10\%$ of the current



Cut-off current characteristic curve



Note: The deviation range of the truncated current curve is $\pm 10\%$ of the peak current